

P/N 1334

Military-Fasteners.com

Description

Length: 1-11/32"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

| SKU / Model: | 1334 |
|-------------------------|---|
| Minimum Qty (MOQ): | 10 EA |
| NSN: | 3120-00-097-1155 |
| Schedule B: | 7318.29.0000 |
| ECCN: | EAR99 |
| National Motor Freight: | 114850, Bearing / Bushing O / T Ball / Roller I / S |



P/N 1334 Specifications

| Overall Length: 1.3450 Inches Minimum And 1.3510 Inches Maximum | |
|--|--|
| | |
| Body Outside Diameter: 0.6510 Inches Minimum And 0.6610 Inches Maximum | |
| Body Inside Diameter: 0.5630 Inches Minimum And 0.5650 Inches Maximum | |
| Left Flange Outside Diameter: 0.7080 Inches Minimum And 0.7100 Inches Maximum | |
| Right Flange Outside Diameter: 0.6820 Inches Minimum And 0.6870 Inches Maximum | |
| Left Flange Width: 0.3125 Inches Nominal | |
| Right Flange Width: 0.1293 Inches Nominal | |
| Lubricant Accommodation Style: Grooved Circular | |
| Corner Shape: Square All Corners | |
| Surface Finish: 20.0 Microinches Outside Diameter Surface Of Left Flange | |
| Surface Finish: 63.0 Microinches Left End Surface Of Body | |
| Surface Groove Location And Quantity: 1 Internal | |
| Material: Nickel Alloy 400 Overall | |
| Material Document And Classification: Qq-n-281,class A Fed Spec Single Material Response Overall | |
| Style Designator: 18c Solid, External Flanges Both Ends | |
| Style Designator: Solid, External Flanges Both Ends | |

How to Order

Order this unknown from our inventory online by visiting <u>https://military-fasteners.com/bushings/sleeve+bushings/1334</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.