

Description

Length: 1-11/32"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	1334
Minimum Qty (MOQ):	10 EA
NSN:	3120-00-097-1155
Schedule B:	7318.29.0000
ECCN:	EAR99
National Motor Freight:	114850, Bearing / Bushing O / T Ball / Roller I / S

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N 1334 Specifications

Overall Length:	1.3450 Inches Minimum And 1.3510 Inches Maximum
Body Outside Diameter:	0.6510 Inches Minimum And 0.6610 Inches Maximum
Body Inside Diameter:	0.5630 Inches Minimum And 0.5650 Inches Maximum
Left Flange Outside Diameter:	0.7080 Inches Minimum And 0.7100 Inches Maximum
Right Flange Outside Diameter:	0.6820 Inches Minimum And 0.6870 Inches Maximum
Left Flange Width:	0.3125 Inches Nominal
Right Flange Width:	0.1293 Inches Nominal
Lubricant Accommodation Style:	Grooved Circular
Corner Shape:	Square All Corners
Surface Finish:	20.0 Microinches Outside Diameter Surface Of Left Flange
Surface Finish:	63.0 Microinches Left End Surface Of Body
Surface Groove Location And Quantity:	1 Internal
Material:	Nickel Alloy 400 Overall
Material Document And Classification:	Qq-n-281,class A Fed Spec Single Material Response Overall
Style Designator:	18c Solid, External Flanges Both Ends
Style Designator:	Solid, External Flanges Both Ends

How to Order

Order this unknown from our inventory online by visiting <https://military-fasteners.com/bushings/sleeve+bushings/1334> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.