

## Description

Fastener Length: 3/8"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	14150312
Minimum Qty (MOQ):	10 EA
NSN:	5320-01-032-8617
Schedule B:	7318.23.0000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N 1415-0312 Specifications

<b>Fastener Length:</b>	0.365 Inches Minimum And 0.385 Inches Maximum
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.095 Inches Minimum And 0.097 Inches Maximum
<b>Shank Style:</b>	Pull Through Hollow Shank
<b>Head Major Diameter:</b>	0.1478 Inches Maximum
<b>Expansion Device:</b>	Mandrel-type C
<b>Grip Length:</b>	0.251 Inches Minimum And 0.312 Inches Maximum
<b>Countersink Angle:</b>	100.0 Degrees Nominal
<b>Material:</b>	Iron Alloy 660 Body
<b>Material:</b>	Iron Alloy 660 Mandrel
<b>Material Document And Classification:</b>	Ams 5737 Assn Std Single Material Response Body
<b>Material Document And Classification:</b>	Ams 5737 Assn Std Single Material Response Mandrel

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/1415-0312> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.