

P/N 145-540-96407

Military-Fasteners.com

#### Description

Fastener Length: 7/8", Hole Diameter: 1/16", Thread: 1/4-20, Thread Length: "

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

### Order this part online

#### **Additional Information**

| SKU / Model:            | 14554096407                               |
|-------------------------|-------------------------------------------|
| Minimum Qty (MOQ):      | 1 EA                                      |
| NSN:                    | 5306-00-825-4422                          |
| Schedule B:             | 7318.15.2010                              |
| ECCN:                   | 9A991                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



# P/N 145-540-96407 Specifications

| Thread Direction:Bigh-handBigh-band0.499 Inches MinimumFrasten Length:0.906 Inches NominalBead Style:HexagonHead Style:0.203 Inches Minimum And 0.234 Inches MaximumHead Height:0.203 Inches Minimum And 0.234 Inches MaximumWidth Between Flats:0.430 Inches Minimum And 0.439 Inches MaximumWidth Between Flats:0.430 Inches Minimum And 0.439 Inches MaximumBole Diameter:0.707 Inches NominalNominal Thread Diameter:0.205 Inches NominalBole Diameter:0.375 Inches NominalHole Quantity:6Orilled-Incension0.376 Inches NominalHole Other StreinDilledHole Type:DilledHole Configuration200 Pounds Per Square InchHole Configuration Style:Hexagon Longitudinal HoleHoard Streingt:Steel Comp Af40 Overall On Steel Comp B630 Overall On Steel Comp B730 Sverall On Steel Comp af40 Overall On Steel Comp Af40 OverallMaterial Document AddResponse Overall On Mile-se050 Mil spec 2nd Material Response Overall On Mile-se050 Mil spec 5th Material Response Overall On Mile-se050                                                                                                                                                                                                                          |                                                      |                                                                                                                                            |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------|
| Thread Length:0.499 Inches MinimumFastener Length:0.906 Inches NominalHead Style:HexagonHead Height:0.203 Inches Minimum And 0.234 Inches MaximumWidth Between Flats:0.430 Inches Minimum And 0.439 Inches MaximumWidth Between Flats:0.430 Inches Minimum And 0.439 Inches MaximumNominal Thread Diameter:0.701 Inches NominalNominal Thread Diameter:0.250 Inches MoninalOutput6Gold Length:0.375 Inches NominalHole Quantity:6Difled Guantity:Inches HeadFastures Provided:Initiade HeadThread Quantity:0.0Colon Construction State HeadHole Configuration State:125000 Pounds Per Square InchHardness Rating:6.0 Rockwell C Maximum Overall And 32.0 Rockwell C Maximum OverallHole Configuration State:Steel Comp 8740 Overall On Steel Comp 8735 Overall On Steel Comp 8740 Overall On Steel Comp 8735 Overall On Steel Comp 4130 Overall On Steel Comp 8740 Overall On Steel Comp 8735 Overall On Steel Comp 4130 Overall On Steel Comp 8740 Overall                                                                                                                                                                                     | Thread Class:                                        | 3a                                                                                                                                         |
| Fastener Length:0.906 Inches NominalHead Style:HexagonHead Style:0.203 Inches Minimum And 0.234 Inches MaximumHead Height:0.203 Inches Minimum And 0.439 Inches MaximumMidth Between Flats:0.400 Inches NominalBole Diametra:0.070 Inches NominalNominal Thread Diametra:0.500 Inches NominalOutput0.375 Inches NominalHole Quantity:6Gol Quantity:6Hole Type:PinledPinled HeadPinledThread Quantity Per Inche2000 Pounds Per Square InchBio Configuration Style:Hexagon Longitudinal Mod 2.0.0 Rockwell C Maximum OverallHole Configuration Style:Steel Comp 8740 Overall On Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4140 Overall Or Steel Comp 8630 Overall Or Miles-6050 Mil Spec 2nd Material Response Overall Or Miles-6050 Miles Spec Sth Material Response Overall Or Miles-6050 Miles Spec Sth Material Response Overall Or Miles-6558 Miles Spec Sth Material Response Overall Or                                                                                                             | Thread Direction:                                    | Right-hand                                                                                                                                 |
| Head Style:HexagonHead Height:0.203 Inches Minimum And 0.234 Inches MaximumWidth Between Flats:0.430 Inches Minimum And 0.439 Inches MaximumHole Diameter:0.070 Inches NominalNominal Thread Diameter:0.250 Inches0.250 Inches Nominal0.250 InchesHole Quantity:0.375 Inches NominalHole Quantity:0.101 Med NominalHole Quantity:0.101 Med NominalHole Type:0.111 Med Med AllHole Type:0.111 Med Med AllHole Type:0.111 Med Med AllHole Cong All All All All All All All All All Al                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | Thread Length:                                       | 0.499 Inches Minimum                                                                                                                       |
| Head Height:0.203 Inches Minimum And 0.234 Inches MaximumWildth Between Flats:0.430 Inches Minimum And 0.439 Inches MaximumHole Daimeter:0.070 Inches NominalNomial Thread Diameter:0.250 Inches NominalBole Quantity:0.375 Inches NominalHole Quantity:6Hole Type:Dialed CallFeatures Provided:Finished HeadBrished Head2500 Nouse PerspectiveMinimum Tensile Strengt:0.500 Nouse PerspectiveBole Configuration Style:Scon Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallHole Configuration Style:Steel Comp 8740 Overall On Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4037 Overall Or Steel Comp 4037 Overall Or Steel Comp 4030 Overall Or Steel Comp 4030 Assn Std 4th Material Response Overall Or Mil-s-6758 Mil Spec Sth Material Response Overall Or Mil-s-6758 Mil Spec Sth Material Response Overall Or Mil-s-6758 Mil Spec Sth Material Response Overall Or Mil-s-6528 Mil Spec Sth Material Response Overall Or Mil-s-6758 Mil Spec Sth Material Response Overall Or Mil-s-6528 Mil Spec Sth Material Response Overall O                            | Fastener Length:                                     | 0.906 Inches Nominal                                                                                                                       |
| Width Between Flats:0.430 Inches Minimu And 0.439 Inches MaximumHole Diameter:0.070 Inches NominalNominal Thread Diameter:0.250 InchesOutput0.375 Inches NominalHole Quantity:6Gold Cuantity:6Hole Type:Drilled HeadThread Quantity Per Inch:20Vance200 Pounds Per Square InchHole Configuration Style:125000 Pounds Per Square InchHole Configuration Style:125000 Pounds Per Square InchHole Configuration Style:126000 Pounds Per Square InchHole Configuration Style:14exagon Longitudinal HoleMaterial:Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall Or Mil-s-6098 Mil Spec 3rd Material Response Overall Or Mil-                                                                                  | Head Style:                                          | Hexagon                                                                                                                                    |
| Hole Diameter:0.070 Inches NominalNominal Thread Diameter:0.250 InchesGrip Length:0.375 Inches NominalHole Quantity:6Hole Oupartity:0Hole Type:DrilledFeatures Provided:Finished HeadThread Quantity Per Inch:202000 Pounds Per Square Inch2500 Nounds Per Square InchHole Configuration Stremeth:26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallHole Configuration Stremeth:Exel Comp 8740 Overall On Steel Comp 8735 Overall Or Steel Comp 4140 Overall On Steel Comp 8735 Overall Or Steel Comp 4140 Overall On Steel Comp 8735 Overall Or Miles-6050 Mil Spec 2nd Material Response Overall Or Miles-6050 Miles Spec 5th Material Response Overall Or Miles-6050 Mile | Head Height:                                         | 0.203 Inches Minimum And 0.234 Inches Maximum                                                                                              |
| Nominal Thread Diameter0.250 InchesGrip Length:0.375 Inches NominalHole Quantity:6Hole Quantity:0PrilledDrilledFeatures Provided:Finished HeadThread Quantity Per Inch:202000 Dounds Per Square Inch125000 Pounds Per Square InchHardness Rating:26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallHole Configuration Style:Hexagon Longitudinal HoleMaterial Comparison Style:Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall OrMaterial Document And<br>Classification:Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Ams 6300 Assn Std 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 4th Material Response Overal                             | Width Between Flats:                                 | 0.430 Inches Minimum And 0.439 Inches Maximum                                                                                              |
| Grip Length:0.375 Inches NominalHole Quantity:6Hole Type:DrilledPreatures Provided:Finished HeadThread Quantity Per Inch:20025000 Pounds Per Square InchHardness Rating:26.0.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallHole Configuration Style:Hexagon Longitudinal HoleMaterial:Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4140 OverallMaterial Document And<br>Classification:Mils-s6049 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-6265 Mil<br>Spec 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-6265 Mil<br>Spec 6th Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallDocument And<br>Classification:Q-q-P-416 Ty2 Cl3 Fed Spec Single Treatment Response Overall                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | Hole Diameter:                                       | 0.070 Inches Nominal                                                                                                                       |
| Hole Quantity:6Hole Type:DrilledFeatures Provided:Finished HeadFread Quantity Per Inch:20Minimum Tensile Strength:125000 Pounds Per Square InchHardness Rating:26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallHole Configuration Style:Hexagon Longitudinal HoleMaterial:Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4037 Overall Or Steel Comp 4130 OverallMaterial Document And<br>Classification:Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 3rd Material<br>Response Overall Or Ams 6300 Assn Std 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-6266 Mil<br>Spec 6th Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment<br>Classification:Qe-p-416 Ty2 Cl3 Fed Spec Single Treatment Response Overall                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | Nominal Thread Diameter:                             | 0.250 Inches                                                                                                                               |
| Hole Type:DrilledFeatures Provided:Finished HeadFeatures Provided:Finished HeadThread Quantity Per Inch:20Minimum Tensile Strength:125000 Pounds Per Square InchHardness Rating:6.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallHole Configuration Style:Hexagon Longitudinal HoleMaterial:Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4140 OverallMaterial Document And<br>Classification:Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-6058 Mil Spec 2nd Material Response Overall Or Ams 6300 Assn 5td 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-5626 Mil<br>Spec 6th Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment And<br>Classification:Q-p-416 Ty2 Cl3 Fed Spec Single Treatment Response Overall                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | Grip Length:                                         | 0.375 Inches Nominal                                                                                                                       |
| Features Provided:Finished HeadFinished Quantity Per Inch:20Minimum Tensile Strength:125000 Pounds Per Square InchHardness Rating:26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallHole Configuration Style:Hexagon Longitudinal HoleMaterial:Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4037 Overall Or Steel Comp 4130 OverallMaterial:Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 3rd MaterialRaterial Document And<br>Classification:Cadmium Overall And Chromate OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment<br>Classification:Q-p-416 Ty2 Cl3 Fed Spec Single Treatment Response Overall                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | Hole Quantity:                                       | 6                                                                                                                                          |
| Thread Quantity Per Inch:20Minimum Tensile Strength:125000 Pounds Per Square InchHardness Rating:26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallHole Configuration Style:Hexagon Longitudinal HoleMaterial:Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or<br>Steel Comp 4140 OverallMaterial:Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 3rd Material<br>Response Overall Or Ams 6300 Assn Std 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-626 Mil<br>Spec 6th Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment:Q-p-416 Ty2 Cl3 Fed Spec Single Treatment Response OverallSurface Treatment And<br>Classification:Q-p-416 Ty2 Cl3 Fed Spec Single Treatment Response Overall                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | Hole Type:                                           | Drilled                                                                                                                                    |
| Minimum Tensile Strength:125000 Pounds Per Square InchHardness Rating:26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallHole Configuration Style:Hexagon Longitudinal HoleMaterial:Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or<br>Steel Comp 4140 OverallMaterial Document And<br>Classification:Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Ams 6300 Assn Std 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-5626 Mil<br>Spec 6th Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallOcument And<br>Classification:Qq-p-416 Ty2 Cl3 Fed Spec Single Treatment Response Overall                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | Features Provided:                                   | Finished Head                                                                                                                              |
| Hardness Rating:26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallHole Configuration Style:Hexagon Longitudinal HoleMaterial:Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or<br>Steel Comp 4140 OverallMaterial Document And<br>Classification:Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 3rd Material<br>Response Overall Or Ams 6300 Assn Std 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-5626 Mil<br>Spec 6th Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment<br>Document And<br>Classification:Qq-p-416 Ty2 Cl3 Fed Spec Single Treatment Response Overall                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | Thread Quantity Per Inch:                            | 20                                                                                                                                         |
| Hole Configuration Style:Hexagon Longitudinal HoleMaterial:Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or<br>Steel Comp 4140 OverallMaterial Document And<br>Classification:Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 3rd Material<br>Response Overall Or Ams 6300 Assn Std 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-5626 Mil<br>Spec 6th Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallQuep-416 Ty2 Cl3 Fed Spec Single Treatment Response OverallQuep-416 Ty2 Cl3 Fed Spec Single Treatment Response Overall                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | Minimum Tensile Strength:                            | 125000 Pounds Per Square Inch                                                                                                              |
| Material:Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or<br>Steel Comp 4140 OverallMaterial Document And<br>Classification:Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 3rd Material<br>Response Overall Or Ams 6300 Assn Std 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-5626 Mil<br>Spec 6th Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment<br>Document And<br>Classification:Qq-p-416 Ty2 Cl3 Fed Spec Single Treatment Response Overall                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | Hardness Rating:                                     | 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall                                                                        |
| Material:Steel Comp 4140 OverallMaterial Document And<br>Classification:Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 3rd Material<br>Response Overall Or Ams 6300 Assn Std 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-5626 Mil<br>Spec 6th Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment<br>Document And<br>Classification:Qq-p-416 Ty2 Cl3 Fed Spec Single Treatment Response Overall                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | Hole Configuration Style:                            | Hexagon Longitudinal Hole                                                                                                                  |
| Material Document And<br>Classification:Response Overall Or Ams 6300 Assn Std 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-5626 Mil<br>Spec 6th Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment<br>Document And<br>Classification:Qq-p-416 Ty2 Cl3 Fed Spec Single Treatment Response Overall                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | Material:                                            |                                                                                                                                            |
| Surface Treatment   Document And Qq-p-416 Ty2 Cl3 Fed Spec Single Treatment Response Overall   Classification:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | Material Document And<br>Classification:             | Response Overall Or Ams 6300 Assn Std 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-5626 Mil |
| Document And Qq-p-416 Ty2 Cl3 Fed Spec Single Treatment Response Overall   Classification: Qq-p-416 Ty2 Cl3 Fed Spec Single Treatment Response Overall                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | Surface Treatment:                                   | Cadmium Overall And Chromate Overall                                                                                                       |
| Thread Series Designator: Unc                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | Surface Treatment<br>Document And<br>Classification: | Qq-p-416 Ty2 Cl3 Fed Spec Single Treatment Response Overall                                                                                |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | Thread Series Designator:                            | Unc                                                                                                                                        |

## How to Order

Order this bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/machine+bolts/145-540-96407</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.