

**Description**

Fastener Length: 1/2",

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	16040412
Minimum Qty (MOQ):	100
NSN:	5320-00-274-8149
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



\* See page 2 for technical characteristics

## P/N 1604-0412 Specifications

<b>Fastener Length:</b>	0.460 Inches Nominal
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.125 Inches Minimum And 0.128 Inches Maximum
<b>Shank Style:</b>	Pull Through Hollow Shank
<b>Head Major Diameter:</b>	0.205 Inches Nominal
<b>Expansion Device:</b>	Plain Stem-type T
<b>Grip Length:</b>	0.250 Inches Maximum
<b>Countersink Angle:</b>	120.0 Degrees Nominal
<b>Material:</b>	Aluminum Alloy 5052 Body
<b>Material:</b>	Steel Mandrel
<b>Surface Treatment:</b>	Phosphate Mandrel

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/1604-0412> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.