## P/N 1926-5-6

### **Description**

Diameter: 7/16", steel overall

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: 192656

Minimum Qty (MOQ): 1 EA

NSN: 5325-00-136-2953

Schedule B: 7318.15.8085

ECCN: N/A

National Motor Freight: 066440, Fasteners Curtain / Snap Metal



<sup>\*</sup> See page 2 for technical characteristics

# P/N 1926-5-6 Specifications

Grip Length:	0.3533 Inches Nominal
Diameter:	0.4289 Inches Minimum And 0.4385 Inches Maximum
Turnlock Stud Shank Style:	Stud Shank
Extension Length:	0.3827 Inches Nominal
Turnlock Stud Head Style:	Flat Fillister
Drive Type:	Socket
Stud Thread Size And Series/type Designator:	0.190-32 Adqbdan Unf
Stud Head Height:	0.023 Inches Minimum And 0.028 Inches Maximum
Stud Shank Major Diameter:	0.311 Inches Minimum And 0.312 Inches Maximum
Material:	Steel Overall
Surface Treatment:	Cadmium Overall

## **How to Order**

Order this sleeve bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/machine+bolts/1926-5-6">https://military-fasteners.com/bolts/machine+bolts/1926-5-6</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.