

**Description**

Diameter: 7/16", steel overall

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	192656
Minimum Qty (MOQ):	1 EA
NSN:	5325-00-136-2953
Schedule B:	7318.15.8085
ECCN:	N/A
National Motor Freight:	066440, Fasteners Curtain / Snap Metal

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N 1926-5-6 Specifications

<b>Grip Length:</b>	0.3533 Inches Nominal
<b>Diameter:</b>	0.4289 Inches Minimum And 0.4385 Inches Maximum
<b>Turnlock Stud Shank Style:</b>	Stud Shank
<b>Extension Length:</b>	0.3827 Inches Nominal
<b>Turnlock Stud Head Style:</b>	Flat Fillister
<b>Drive Type:</b>	Socket
<b>Stud Thread Size And Series/type Designator:</b>	0.190-32 Adqbdan Unf
<b>Stud Head Height:</b>	0.023 Inches Minimum And 0.028 Inches Maximum
<b>Stud Shank Major Diameter:</b>	0.311 Inches Minimum And 0.312 Inches Maximum
<b>Material:</b>	Steel Overall
<b>Surface Treatment:</b>	Cadmium Overall

## How to Order

Order this sleeve bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/1926-5-6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.