

Description

Diameter: 7/16", steel overall

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|--|
| SKU / Model: | 192656 |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5325-00-136-2953 |
| Schedule B: | 7318.15.8085 |
| ECCN: | N/A |
| National Motor Freight: | 066440, Fasteners Curtain / Snap Metal |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N 1926-5-6 Specifications

| | |
|---|---|
| Grip Length: | 0.3533 Inches Nominal |
| Diameter: | 0.4289 Inches Minimum And 0.4385 Inches Maximum |
| Turnlock Stud Shank Style: | Stud Shank |
| Extension Length: | 0.3827 Inches Nominal |
| Turnlock Stud Head Style: | Flat Fillister |
| Drive Type: | Socket |
| Stud Thread Size And Series/type Designator: | 0.190-32 Adqbdan Unf |
| Stud Head Height: | 0.023 Inches Minimum And 0.028 Inches Maximum |
| Stud Shank Major Diameter: | 0.311 Inches Minimum And 0.312 Inches Maximum |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall |

How to Order

Order this sleeve bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/1926-5-6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.