

P/N 20-057-5-19D

Description

Fastener Length: 1-21/32", Thread: 1/4-24, Thread Length: 15/32", 20-057 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

NAS1305-19D

SKU / Model: 20057519D

Minimum Qty (MOQ): 5

NSN: 5306-00-978-8063

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









P/N 20-057-5-19D Specifications

Thread Direction: Right-hand Thread Direction: Night-hand Thread Length: 0.469 Inches Minimum Fastener Length: 1.657 Inches Nominal Head Style: Dished Hexagon Head Height: 0.156 Inches Nominal Width Between Flats: 0.492 Inches Minimum And 0.502 Inches Maximum Grip Diameter: 0.3110 Inches Minimum And 0.3120 Inches Maximum Shank Unthreaded Hole Diameter: 0.3110 Inches Minimum And 0.3120 Inches Maximum Shank Unthreaded Hole Diameter: 0.076 Inches Nominal First Hole Slingle Shear Strength: 96000 Pounds Per Square Inch Nominal Thread Diameter: 0.312 Inches Grip Length: 1.88 Inches Nominal Thread Quantity Per Inch: 24 Minimum Tensile Strength: 160000 Pounds Per Square Inch Distance From Head Largest Bearing Surface To Shank Hole Center: Seel Comp 4140 Overall And 40.0 Rockwell C Maximum Overall Overall Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Oo-p-416.tv 2 Cl 2 Fed Spec Sindle Treatment Response Overall Surface Treatment Document And		
Thread Length: Fastener Length: 1.657 Inches Nominal Head Style: Dished Hexagon Head Height: 0.156 Inches Nominal Width Between Flats: O.492 Inches Minimum And 0.502 Inches Maximum Grip Diameter: 0.3110 Inches Minimum And 0.3120 Inches Maximum Grip Diameter: 0.3110 Inches Minimum And 0.3120 Inches Maximum Shank Unthreaded Hole Diameter: 0.076 Inches Nominal First Hole Single Shear Strength: 96000 Pounds Per Square Inch Nominal Thread Diameter: 0.312 Inches Grip Length: 1.188 Inches Nominal Thread Quantity Per Inch: 4 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 34.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: Material: Material Document And Classification: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Overall Surface Treatment: Ocen-416 ty 2 C12 Fed Spec Single Treatment Response Overall Ocen-416 ty 2 C12 Fed Spec Single Treatment Response Overall Ocen-416 ty 2 C12 Fed Spec Single Treatment Response Overall Ocen-416 ty 2 C12 Fed Spec Single Treatment Response Overall Ocen-416 ty 2 C12 Fed Spec Single Treatment Response Overall Ocen-416 ty 2 C12 Fed Spec Single Treatment Response Overall Ocen-416 ty 2 C12 Fed Spec Single Treatment Response Overall Ocen-416 ty 2 C12 Fed Spec Single Treatment Response Overall Ocen-416 ty 2 C12 Fed Spec Single Treatment Response Overall Ocen-416 ty 2 C12 Fed Spec Single Treatment Response Overall Ocen-416 ty 2 C12 Fed Spec Single Treatment Response Overall Ocen-416 ty 2 C12 Fed Spec Single Treatment Response Overall Ocen-416 ty 2 C12 Fed Spec Single Treatment Response Overall Ocen State Style St	Thread Class:	3a
Fastener Length: Head Style: Dished Hexagon Head Height: 0.156 Inches Nominal Width Between Flats: 0.492 Inches Minimum And 0.502 Inches Maximum Grip Diameter: 0.3110 Inches Minimum And 0.3120 Inches Maximum Grip Diameter: 0.310 Inches Minimum And 0.3120 Inches Maximum O.076 Inches Nominal First Hole Single Shear Strength: 96000 Pounds Per Square Inch Nominal Thread Diameter: 0.312 Inches Grip Length: 1.188 Inches Nominal Thread Quantity Per Inch: 44 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 34.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall 1.476 Inches Nominal First Hole Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Material Document And Classification: Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall On-p-416 by 2 Cl 2 Fed Spec Single Treatment Response Overall On-p-416 by 2 Cl 2 Fed Spec Single Treatment Response Overall	Thread Direction:	Right-hand
Head Style: Dished Hexagon Head Height: 0.156 Inches Nominal Width Between Flats: 0.492 Inches Minimum And 0.502 Inches Maximum Grip Diameter: 0.3110 Inches Minimum And 0.3120 Inches Maximum Shank Unthreaded Hole Diameter: 0.076 Inches Nominal First Hole Single Shear Strength: 96000 Pounds Per Square Inch Nominal Thread Diameter: 0.312 Inches Grip Length: 1.188 Inches Nominal Thread Quantity Per Inch: 24 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 34.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: Steel Comp 4140 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Material Document And Classification: Surface Treatment Document And One-p-416 by 2 Cl 2 Fed Sper Single Treatment Response Overall Surface Treatment Document And One-p-416 by 2 Cl 2 Fed Sper Single Treatment Response Overall Surface Treatment Document And One-p-416 by 2 Cl 2 Fed Sper Single Treatment Response Overall Surface Treatment Document And One-p-416 by 2 Cl 2 Fed Sper Single Treatment Response Overall Surface Treatment Document And One-p-416 by 2 Cl 2 Fed Sper Single Treatment Response Overall Surface Treatment Document And One-p-416 by 2 Cl 2 Fed Sper Single Treatment Response Overall Surface Treatment: One-p-416 by 2 Cl 2 Fed Sper Single Treatment Response Overall	Thread Length:	0.469 Inches Minimum
Head Height: 0.156 Inches Nominal Width Between Flats: 0.492 Inches Minimum And 0.502 Inches Maximum Grip Diameter: 0.3110 Inches Minimum And 0.3120 Inches Maximum Shank Unthreaded Hole Diameter: 0.076 Inches Nominal First Hole Single Shear Strength: 96000 Pounds Per Square Inch Nominal Thread Diameter: 0.312 Inches Grip Length: 1.188 Inches Nominal Thread Quantity Per Inch: 24 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 34.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: 5teel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Material Document And Classification: 5teel Material Response Overall Or Mil-s-6098 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Ogen-416 to 2 C12 Fed Spec Single Treatment Response Overall	Fastener Length:	1.657 Inches Nominal
Width Between Flats: 0.492 Inches Minimum And 0.502 Inches Maximum Grip Diameter: 0.3110 Inches Minimum And 0.3120 Inches Maximum Shank Unthreaded Hole Diameter: 0.076 Inches Nominal First Hole Single Shear Strength: 96000 Pounds Per Square Inch Nominal Thread Diameter: 0.312 Inches Grip Length: 1.88 Inches Nominal Thread Quantity Per Inch: 24 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 34.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Material Document And Classification: Will-s-6026 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Respons	Head Style:	Dished Hexagon
Grip Diameter: 0.3110 Inches Minimum And 0.3120 Inches Maximum 0.076 Inches Nominal First Hole Single Shear Strength: 96000 Pounds Per Square Inch 0.312 Inches Grip Length: 1.188 Inches Nominal Thread Quantity Per Inch: 44 Minimum Tensile Strength: 160000 Pounds Per Square Inch 160000 Pounds Per S	Head Height:	0.156 Inches Nominal
Shank Unthreaded Hole Diameter: Single Shear Strength: 96000 Pounds Per Square Inch Nominal Thread Diameter: 0.312 Inches Grip Length: 1.188 Inches Nominal Thread Quantity Per Inch: 44 Minimum Tensile Strength: 160000 Pounds Per Square Inch 160000 Pounds Per Square Inch 44.0 Rockwell C Minimum Overall At Rockwell C Minimum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Og-p-416 by 2 Cl 2 Fed Spec Single Treatment Response Overall Og-p-416 by 2 Cl 2 Fed Spec Single Treatment Response Overall	Width Between Flats:	0.492 Inches Minimum And 0.502 Inches Maximum
Single Shear Strength: 96000 Pounds Per Square Inch Nominal Thread Diameter: 0.312 Inches Grip Length: 1.188 Inches Nominal Thread Quantity Per Inch: 24 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 34.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: 34.0 Rockwell C Moverall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Material Document And Classification: Material Response Overall Or Mil-s-6098 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Og-p-416.ty 2 CL2 Fed Spec Single Treatment Response Overall	Grip Diameter:	0.3110 Inches Minimum And 0.3120 Inches Maximum
Nominal Thread Diameter: Grip Length: 1.188 Inches Nominal Thread Quantity Per Inch: 24 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 34.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: Naterial: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Og-p-416 ty 2 CL2 Fed Spec Single Treatment Response Overall	Shank Unthreaded Hole Diameter:	0.076 Inches Nominal First Hole
Grip Length: Thread Quantity Per Inch: Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 34.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Document And Classification: Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Og-p-416 ty 2 Cl 2 Fed Spec Single Treatment Response Overall	Single Shear Strength:	96000 Pounds Per Square Inch
Thread Quantity Per Inch: Minimum Tensile Strength: 160000 Pounds Per Square Inch 34.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Respo	Nominal Thread Diameter:	0.312 Inches
Minimum Tensile Strength: Hardness Rating: 34.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Og-9-416.ty 2 CL2 Fed Spec Single Treatment Response Overall	Grip Length:	1.188 Inches Nominal
Hardness Rating: Distance From Head Largest Bearing Surface To Shank Hole Center: Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Document And Classification: Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Oq-p-416 ty 2 Cl 2 Fed Spec Single Treatment Response Overall	Thread Quantity Per Inch:	24
Distance From Head Largest Bearing Surface To Shank Hole Center: Material: Material: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Og-p-416.ty 2 CL2 Fed Spec Single Treatment Response Overall	Minimum Tensile Strength:	160000 Pounds Per Square Inch
Surface To Shank Hole Center: Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Og-p-416 ty 2 CL2 Fed Spec Single Treatment Response Overall	Hardness Rating:	34.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Material: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Document And Classification: Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Og-p-416.ty 2 Cl 2 Fed Spec Single Treatment Response Overall		1.476 Inches Nominal First Hole
Material Document And Classification: Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Og-p-416.ty 2 Cl 2 Fed Spec Single Treatment Response Overall	Material:	
Surface Treatment Document And Og-p-416.ty 2 Cl 2 Fed Spec Single Treatment Response Overall	Material Document And Classification:	Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response
Og-p-416.ty 2 CL2 Fed Spec Single Treatment Response Overall	Surface Treatment:	Cadmium Overall And Chromate Overall
Classification:	Surface Treatment Document And Classification:	Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator: Unf	Thread Series Designator:	Unf

How to Order

Order this machine bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/20-057-5-19D and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/machine+bolts/20-057-5-19D and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/machine+bolts/20-057-5-19D and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/machine+bolts/20-057-5-19D and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/machine+bolts/20-057-5-19D and selecting the quantity you want of the property of the