

Description

Fastener Length: 3-3/64", Thread: 5/8-18, Thread Length: 15/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	2006510034
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-057-3048
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N 20-065-10034 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.899 Inches Minimum And 0.939 Inches Maximum
Fastener Length:	3.034 Inches Minimum And 3.054 Inches Maximum
Head Style:	Double Hexagon W/hole
Head Height:	0.608 Inches Minimum And 0.628 Inches Maximum
Width Between Flats:	0.678 Inches Minimum And 0.698 Inches Maximum
Extended Washer Diameter:	1.040 Inches Minimum And 1.050 Inches Maximum
Extended Washer Thickness:	0.140 Inches Minimum And 0.160 Inches Maximum
Grip Diameter:	0.6230 Inches Minimum And 0.6240 Inches Maximum
Nominal Thread Diameter:	0.625 Inches
Grip Length:	2.115 Inches Minimum And 2.135 Inches Maximum
Thread Quantity Per Inch:	18
Minimum Tensile Strength:	180000 Pounds Per Square Inch
Hardness Rating:	39.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall
Material:	Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 6150 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/20-065-10034> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.