

**Description**

Fastener Length: 1-63/64", Thread: 3/8-24, Head Width: 1/4", Thread Length: 1-13/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	200976F32Z
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-420-0048
Schedule B:	7318.15.2010
ECCN:	9A991

NO IMAGE  
AVAILABLE

## P/N 20097-6F-32Z Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	1.500 Inches Minimum And 1.813 Inches Maximum
<b>Fastener Length:</b>	1.960 Inches Minimum And 2.000 Inches Maximum
<b>Head Style:</b>	Knurled No. 5
<b>Head Diameter:</b>	0.550 Inches Minimum And 0.562 Inches Maximum
<b>Head Height:</b>	0.368 Inches Minimum And 0.375 Inches Maximum
<b>Internal Drive Style:</b>	Hexagon
<b>Nominal Thread Diameter:</b>	0.375 Inches
<b>Width Across Flats:</b>	0.312 Inches Nominal
<b>Thread Quantity Per Inch:</b>	24
<b>Hardness Rating:</b>	38.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall
<b>Minimum Yield Strength:</b>	150000 Pounds Per Square Inch
<b>Material:</b>	Steel Uns K03104 Overall
<b>Material Document And Classification:</b>	Astm A574 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Zinc Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Astm B633, Type 2 Assn Std All Treatment Responses Overall
<b>Thread Series Designator:</b>	Unrf

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/20097-6F-32Z> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.