

**Description**

Fastener Length: 1-63/64", Thread: 3/8-24, Head Width: 1/4", Thread Length: 1-13/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                    |                  |
|--------------------|------------------|
| SKU / Model:       | 200976F32Z       |
| Minimum Qty (MOQ): | 5 EA             |
| NSN:               | 5305-01-420-0048 |
| Schedule B:        | 7318.15.2010     |
| ECCN:              | 9A991            |

NO IMAGE  
AVAILABLE

## P/N 20097-6F-32Z Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>                                  | 3a  |
| <b>Thread Direction:</b>                              | Right-hand  |
| <b>Thread Length:</b>                                 | 1.500 Inches Minimum And 1.813 Inches Maximum                       |
| <b>Fastener Length:</b>                               | 1.960 Inches Minimum And 2.000 Inches Maximum                       |
| <b>Head Style:</b>                                    | Knurled No. 5   |
| <b>Head Diameter:</b>                                 | 0.550 Inches Minimum And 0.562 Inches Maximum                       |
| <b>Head Height:</b>                                   | 0.368 Inches Minimum And 0.375 Inches Maximum                       |
| <b>Internal Drive Style:</b>                          | Hexagon   |
| <b>Nominal Thread Diameter:</b>                       | 0.375 Inches  |
| <b>Width Across Flats:</b>                            | 0.312 Inches Nominal  |
| <b>Thread Quantity Per Inch:</b>                      | 24  |
| <b>Hardness Rating:</b>                               | 38.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall |
| <b>Minimum Yield Strength:</b>                        | 150000 Pounds Per Square Inch                                       |
| <b>Material:</b>                                      | Steel Uns K03104 Overall  |
| <b>Material Document And Classification:</b>          | Astm A574 Assn Std Single Material Response Overall                 |
| <b>Surface Treatment:</b>                             | Zinc Overall And Chromate Overall                                   |
| <b>Surface Treatment Document And Classification:</b> | Astm B633, Type 2 Assn Std All Treatment Responses Overall          |
| <b>Thread Series Designator:</b>                      | Unrf  |

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/20097-6F-32Z> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.