

Description

Fastener Length: 1-63/64", Thread: 3/8-24, Head Width: 1/4", Thread Length: 1-13/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	200976F32Z
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-420-0048
Schedule B:	7318.15.2010
ECCN:	9A991



* See page 2 for technical characteristics

P/N 20097-6F-32Z Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.500 Inches Minimum And 1.813 Inches Maximum
Fastener Length:	1.960 Inches Minimum And 2.000 Inches Maximum
Head Style:	Knurled No. 5
Head Diameter:	0.550 Inches Minimum And 0.562 Inches Maximum
Head Height:	0.368 Inches Minimum And 0.375 Inches Maximum
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.375 Inches
Width Across Flats:	0.312 Inches Nominal
Thread Quantity Per Inch:	24
Hardness Rating:	38.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall
Minimum Yield Strength:	150000 Pounds Per Square Inch
Material:	Steel Uns K03104 Overall
Material Document And Classification:	Astm A574 Assn Std Single Material Response Overall
Surface Treatment:	Zinc Overall And Chromate Overall
Surface Treatment Document And Classification:	Astm B633, Type 2 Assn Std All Treatment Responses Overall
Thread Series Designator:	Unrf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/20097-6F-32Z> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.