

Description

Fastener Length: 3-5/16", Thread: 1/2-20, Thread Length: 51/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	204135551
Minimum Qty (MOQ):	1
NSN:	5305-01-019-0758
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N 204-13555-1 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.802 Inches Nominal
Fastener Length:	3.340 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.717 Inches Nominal
Grip Diameter:	0.4985 Inches Minimum And 0.4995 Inches Maximum
Internal Drive Style:	High-torque
Nominal Thread Diameter:	0.500 Inches
Grip Length:	2.438 Inches Nominal
Thread Quantity Per Inch:	20
Countersink Angle:	100.0 Degrees Nominal
Surface Finish:	32.0 Microinches Threads
Surface Finish:	63.0 Microinches Grip
Material:	Steel Overall
Material Document And Classification:	Ph13-8mo Bms7-189 Fscm 81205 Mfr Ref Single Material Response Overall
Thread Series Designator:	Unjf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/204-13555-1> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.