

Description

Subminiature basic switch, single pole double throw, pin plunger actuator, solder termination, 21SX series switch

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[MS24547-1](#)

SKU / Model:	21SX39T
Minimum Qty (MOQ):	1
NSN:	5930-00-803-4570
Schedule B:	8535.30.0080
ECCN:	9A991
National Motor Freight:	061300, Circuit Breaker / Switch Noi



\* See page 2 for technical characteristics

# P/N 21SX39-T Specifications

Body Style:	Hole Mounted
Hazardous Locations/environmental Protection:	Dustproof
Overall Length:	0.510 Inches Maximum
Center To Center Distance Between Mounting Facilities Parallel To Length:	0.186 Inches Minimum And 0.190 Inches Maximum
Overall Height:	0.500 Inches Nominal
Overall Width:	0.210 Inches Maximum
Body Length:	0.510 Inches Maximum
Body Width:	0.210 Inches Maximum
Body Height:	0.340 Inches Minimum And 0.360 Inches Maximum
Case Material:	Plastic
Unthreaded Mounting Hole Diameter:	0.087 Inches Minimum And 0.090 Inches Maximum
Actuator Style:	Round
Actuator Diameter:	0.057 Inches Minimum And 0.067 Inches Maximum
Actuator Height:	0.080 Inches Nominal
Actuator Free Position Height:	0.305 Inches Minimum And 0.335 Inches Maximum
Maximum Voltage Rating In Volts:	115.0 Ac And 28.0 Dc
Inclosure Type:	Fully Inclosed
Mounting Method:	Unthreaded Hole
Nonpile-up Contact Arrangement:	1 Pole, Double Throw, One Position Momentary Single Switch Unit
Switch Release Force:	1.0 Ounces Minimum
Switch Actuating Force:	5.0 Ounces Maximum
Actuator Movement:	0.020 Pretravel Inches Maximum And 0.004 Overtravel Inches Minimum And 0.005 Differential Inches Maximum
Contact Load Current Rating At Maximum Rated Voltage:	7.000 Amperes Resistive Dc And 4.000 Amperes Inductive Dc And 2.500 Amperes Lamp Dc And 7.000 Amperes Resistive Ac And 7.000 Amperes Inductive Ac And 2.000 Amperes Lamp Ac
Test Data Document:	81349-mil-prf-8805 Specification (includes Engineering Type Bulletins, Brochures,etc., That Reflect Specification Type Data In Specification Format; Excludes Commercial Catalogs, Industry Directories, And Similar Trade Publications, Reflecting General Type Data On Certain Environmental And Performance Requirements And Test Conditions That Are Shown As "typical", "average", "nominal", Etc.).
Terminal Type And Quantity:	3 Turret
Specification/standard Data:	96906-ms24547 Government Standard

## How to Order

Order this sensitive switch from our inventory online by visiting <https://military-fasteners.com/switches/sensitive+switch/21SX39-T> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.