

**Description**

Subminiature basic switch, single pole double throw, pin plunger actuator, solder termination, 21SX series switch

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[MS24547-1](#)

SKU / Model:	21SX39T
Minimum Qty (MOQ):	1
NSN:	5930-00-803-4570
Schedule B:	8535.30.0080
ECCN:	9A991
National Motor Freight:	061300, Circuit Breaker / Switch Noi



\* See page 2 for technical characteristics

# P/N 21SX39-T Specifications

<b>Body Style:</b>	Hole Mounted
<b>Hazardous Locations/environmental Protection:</b>	Dustproof
<b>Overall Length:</b>	0.510 Inches Maximum
<b>Center To Center Distance Between Mounting Facilities Parallel To Length:</b>	0.186 Inches Minimum And 0.190 Inches Maximum
<b>Overall Height:</b>	0.500 Inches Nominal
<b>Overall Width:</b>	0.210 Inches Maximum
<b>Body Length:</b>	0.510 Inches Maximum
<b>Body Width:</b>	0.210 Inches Maximum
<b>Body Height:</b>	0.340 Inches Minimum And 0.360 Inches Maximum
<b>Case Material:</b>	Plastic
<b>Unthreaded Mounting Hole Diameter:</b>	0.087 Inches Minimum And 0.090 Inches Maximum
<b>Actuator Style:</b>	Round
<b>Actuator Diameter:</b>	0.057 Inches Minimum And 0.067 Inches Maximum
<b>Actuator Height:</b>	0.080 Inches Nominal
<b>Actuator Free Position Height:</b>	0.305 Inches Minimum And 0.335 Inches Maximum
<b>Maximum Voltage Rating In Volts:</b>	115.0 Ac And 28.0 Dc
<b>Inclosure Type:</b>	Fully Inclosed
<b>Mounting Method:</b>	Unthreaded Hole
<b>Nonpile-up Contact Arrangement:</b>	1 Pole, Double Throw, One Position Momentary Single Switch Unit
<b>Switch Release Force:</b>	1.0 Ounces Minimum
<b>Switch Actuating Force:</b>	5.0 Ounces Maximum
<b>Actuator Movement:</b>	0.020 Pretravel Inches Maximum And 0.004 Overtravel Inches Minimum And 0.005 Differential Inches Maximum
<b>Contact Load Current Rating At Maximum Rated Voltage:</b>	7.000 Amperes Resistive Dc And 4.000 Amperes Inductive Dc And 2.500 Amperes Lamp Dc And 7.000 Amperes Resistive Ac And 7.000 Amperes Inductive Ac And 2.000 Amperes Lamp Ac
<b>Test Data Document:</b>	81349-mil-prf-8805 Specification (includes Engineering Type Bulletins, Brochures,etc., That Reflect Specification Type Data In Specification Format; Excludes Commercial Catalogs, Industry Directories, And Similar Trade Publications, Reflecting General Type Data On Certain Environmental And Performance Requirements And Test Conditions That Are Shown As "typical", "average", "nominal", Etc.).
<b>Terminal Type And Quantity:</b>	3 Turret
<b>Specification/standard Data:</b>	96906-ms24547 Government Standard

## How to Order

Order this sensitive switch from our inventory online by visiting <https://military-fasteners.com/switches/sensitive+switch/21SX39-T> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.