

P/N 22996-16

Description

Fastener Length: 3/16"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: 2299616

Minimum Qty (MOQ): 5 EA

NSN: 5305-00-053-1111

Schedule B: 7318.15.6080

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N 22996-16 Specifications

Fastener Length:	0.157 Inches Minimum And 0.188 Inches Maximum
Head Style:	Pan
Head Diameter:	0.205 Inches Minimum And 0.219 Inches Maximum
Head Height:	0.070 Inches Minimum And 0.080 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
End Item Identification:	W/s:engine, Aircraft, F-108 (cfm-56, Kc-135a); M1a2 Abrams Tank, 2350-01-328-5964 (eaa-cmbt85pk3); Engine, Aircraft, F100-pw-100 (f-15a/b/c/d); Engine, Aircraft Tf33-pw-102 (c-135e, Ec-135h/k/p); Aircraft, Awacs, E-3a; Engine, Aircraft, Tf39-ge-1 (c-5a); Aircraft (ac130-h, Mc-130h, Ec-130e, Hc-130); Engine, Aircraft, F100-pw-200 (f-16a/b/c/d); Helicopter, Mh-53e; Engine, Aircraft, Tf-33-p-7 (c-141a/b)
Features Provided:	Casehardened
Nonmachine Thread Style:	Dog Type (type B Or C)
Nonmachine Nominal Thread Diameter:	0.112 Inches
Material:	Steel Comp 1016 Overall Or Steel Comp 1018 Overall Or Steel Comp 1019 Overall Or Steel Comp 1021 Overall Or Steel Comp 1022 Overall Or Steel Comp 1524 Overall
Material Document And Classification:	Aisi Assn Std All Material Responses Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall

How to Order

Order this screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/22996-16 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.