

## P/N 22K1-054

## **Description**

Thread Size: 1/4", Nut Height: 5/8", Head Width: 1/2

\* Manufacturer certifications are shipped with your order EREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: 22K1054

Minimum Qty (MOQ): 20

NSN: 5310-00-274-8323

Schedule B: 7318.16.0085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N 22K1-054 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque With Nonmetallic Insert
Nut Style:	Сар
Nut Height:	0.594 Inches Nominal
Width Across Flats:	0.562 Inches Nominal
Temp Rating:	250.0 Deg Fahrenheit Nominal
Thread Series:	Unf
Thread Quantity Per Inch:	24
Nominal Thread Size:	0.312 Inches
Bearing Surface Type:	Chamfered
Material:	Steel Comp 1212 Overall Except Insert
Material Document And Classification:	Fed-std-66 Fed Std All Material Responses Overall Except Insert
Surface Treatment:	Cadmium Overall Except Insert

### **How to Order**

Order this self-locking cap nut from our inventory online by visiting <a href="https://military-fasteners.com/nuts/self\_locking+cap+nuts/22K1-054">https://military-fasteners.com/nuts/self\_locking+cap+nuts/22K1-054</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/nuts/self\_locking+cap+nuts/22K1-054">https://military-fasteners.com/nuts/self\_locking+cap+nuts/22K1-054</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/nuts/self\_locking+cap+nuts/22K1-054">https://military-fasteners.com/nuts/self\_locking+cap+nuts/22K1-054</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/nuts/self\_locking+cap+nuts/22K1-054">https://military-fasteners.com/nuts/self\_locking+cap+nuts/22K1-054</a> and selecting the quantity of the property of the pr