

Description

Thread Size: 1/8", Nut Height: 3/8", Head Width: 3/8

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | 22K182 |
| Minimum Qty (MOQ): | 20 |
| NSN: | 5310-00-222-4245 |
| Schedule B: | 7318.16.0085 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N 22K1-82 Specifications

| | |
|---|--|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Locking Feature: | Prevailing Torque With Nonmetallic Insert |
| Nut Style: | Cap |
| Nut Height: | 0.329 Inches Minimum And 0.359 Inches Maximum |
| Width Across Flats: | 0.365 Inches Minimum And 0.377 Inches Maximum |
| Temp Rating: | 250.0 Deg Fahrenheit Nominal |
| Thread Series: | Unc |
| Thread Quantity Per Inch: | 32 |
| Nominal Thread Size: | 0.164 Inches |
| Bearing Surface Type: | Washer Faced |
| Material: | Steel Comp 12L14 Nut |
| Surface Treatment: | Cadmium Cap |
| Surface Treatment: | Cadmium Nut |
| Surface Treatment Document And Classification: | Qq-p-416,type 1,class 3 Fed Spec Single Treatment Response Cap |

How to Order

Order this self-locking cap nut from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+cap+nuts/22K1-82 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.