

Description

length: 0.590", zinc trivalent clear finish, cadmium plated steel, slotted recess, 2351-20-36 series stud

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	23512036Z3CT
Minimum Qty (MOQ):	10
NSN:	5325-00-821-4253
ECCN:	EAR99
National Motor Freight:	066440, Fasteners Curtain / Snap Metal



\* See page 2 for technical characteristics

## P/N 2351-20-36-Z3CT Specifications

<b>Grip Length:</b>	0.580 Inches Minimum And 0.600 Inches Maximum
<b>Diameter:</b>	0.370 Inches Minimum And 0.375 Inches Maximum
<b>Turnlock Stud Shank Style:</b>	Stud Shank
<b>Turnlock Stud Head Style:</b>	Fillister
<b>Material Accommodated Thickness:</b>	0.351 Inches Minimum And 0.360 Inches Maximum
<b>Drive Type:</b>	Slotted
<b>Shank Neck Length:</b>	0.440 Inches Minimum And 0.460 Inches Maximum
<b>Stud Shank Major Diameter:</b>	0.212 Inches Minimum And 0.217 Inches Maximum
<b>Material:</b>	Steel Overall
<b>Surface Treatment:</b>	Cadmium Overall

## How to Order

Order this turnlock fastener stud from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+studs/2351-20-36-Z3CT> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.