

**Description**

cad plated steel - grip length: 0.480", stud shank, fillister wing head - material accomodated thickness 0.241 - 0.250"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	2351W2027C3C
Minimum Qty (MOQ):	1
NSN:	5325-00-425-5322
National Motor Freight:	095190, Hardware, Noi Sub 9

NO IMAGE  
AVAILABLE

## P/N 2351-W20-27-C3C Specifications

<b>Grip Length:</b>	0.480 Inches Nominal
<b>Head Length:</b>	0.865 Inches Minimum And 0.875 Inches Maximum
<b>Securing Device Type:</b>	Ring
<b>Turnlock Stud Shank Style:</b>	Stud Shank
<b>Turnlock Stud Head Style:</b>	Fillister Wing
<b>Material Accommodated Thickness:</b>	0.241 Inches Minimum And 0.250 Inches Maximum
<b>Shank Neck Length:</b>	0.330 Inches Nominal
<b>Stud Head Height:</b>	0.312 Inches Nominal
<b>Stud Shank Major Diameter:</b>	0.212 Inches Minimum And 0.217 Inches Maximum
<b>Material:</b>	Steel Overall Or Steel Comp 8620 Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416 Type 1 Class 2 Fed Spec Single Treatment Response Overall

## How to Order

Order this turnlock fastener stud from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+studs/2351-W20-27-C3C> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.