

P/N 2351-W20-27-C3C

Military-Fasteners.com

Description

cad plated steel - grip length: 0.480", stud shank, fillister wing head - material accomodated thickness 0.241 - 0.250"

* Manufacturer certifications are shipped with your order $\underline{\mathsf{FREE}}$ of charge

Order this part online

Additional Information

SKU / Model:	2351W2027C3C
Minimum Qty (MOQ):	1
NSN:	5325-00-425-5322
National Motor Freight:	095190, Hardware, Noi Sub 9



P/N 2351-W20-27-C3C Specifications

Grip Length:	0.480 Inches Nominal
Head Length:	0.865 Inches Minimum And 0.875 Inches Maximum
Securing Device Type:	Ring
Turnlock Stud Shank Style:	Stud Shank
Turnlock Stud Head Style:	Fillister Wing
Material Accommodated Thickness:	0.241 Inches Minimum And 0.250 Inches Maximum
Shank Neck Length:	0.330 Inches Nominal
Stud Head Height:	0.312 Inches Nominal
Stud Shank Major Diameter:	0.212 Inches Minimum And 0.217 Inches Maximum
Material:	Steel Overall Or Steel Comp 8620 Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416 Type 1 Class 2 Fed Spec Single Treatment Response Overall

How to Order

Order this turnlock fastener stud from our inventory online by visiting <u>https://military-fasteners.com/studs/turnlock+fastener+studs/2351-W20-27-C3C</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.