

Description

turnlock fastener stud part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	2351W2054C3C
Minimum Qty (MOQ):	5
NSN:	5325-00-297-9637
National Motor Freight:	095190, Hardware, Noi

NO IMAGE
AVAILABLE

P/N 2351-W20-54-C3C Specifications

Grip Length:	0.760 Inches Minimum And 0.770 Inches Maximum
Head Length:	0.865 Inches Minimum And 0.875 Inches Maximum
Securing Device Type:	Ring
Turnlock Stud Shank Style:	Stud Shank
Turnlock Stud Head Style:	Fillister Wing
Material Accommodated Thickness:	0.511 Inches Minimum And 0.540 Inches Maximum
Drive Type:	Slotted
Shank Neck Length:	0.520 Inches Minimum And 0.540 Inches Maximum
Stud Head Height:	0.312 Inches Nominal
Stud Shank Major Diameter:	0.212 Inches Minimum And 0.217 Inches Maximum
Material:	Steel Comp 2317 Overall Or Steel Comp 8620 Overall
Material Document And Classification:	Sae Assn Std 1st Material Response Overall Or Aisi Assn Std 2nd Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 1,cl 2 Fed Spec Single Treatment Response Overall
Nondefinitive Spec/std Data:	3 Type And 1 Style And A Class Or B Class And 2 Size

How to Order

Order this turnlock fastener stud from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+studs/2351-W20-54-C3C> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.