

Description

Fastener Length: 1/2", Hole Diameter: 1/16", Thread: 5/16-24, Thread Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | 237233 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5306-00-207-7963 |
| Schedule B: | 7318.15.8085 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N 237233 Specifications

| | |
|--|---|
| Thread Direction: | Right-hand |
| Thread Length: | 0.490 Inches Minimum And 0.510 Inches Maximum |
| Fastener Length: | 0.490 Inches Minimum And 0.510 Inches Maximum |
| Head Style: | Double Hexagon W/hole |
| Head Height: | 0.334 Inches Minimum And 0.354 Inches Maximum |
| Width Between Flats: | 0.362 Inches Minimum And 0.377 Inches Maximum |
| Extended Washer Diameter: | 0.490 Inches Minimum And 0.510 Inches Maximum |
| Extended Washer Thickness: | 0.070 Inches Minimum And 0.090 Inches Maximum |
| Hole Diameter: | 0.062 Inches Nominal |
| Nominal Thread Diameter: | 0.312 Inches |
| Hole Quantity: | 4 |
| Hole Type: | Drilled |
| Features Provided: | Finished Head |
| Nonstandard Thread Pitch Diameter: | +0.2797/+0.2824 Inches |
| Nonstandard Thread Pitch Diameter: | +0.2797 To 0.2824 Inches |
| Thread Quantity Per Inch: | 24 |
| Hardness Rating: | 30.0 Rockwell C Minimum Overall And 38.0 Rockwell C Maximum Overall |
| Hole Configuration Style: | Hexagon Longitudinal Hole |
| Material: | Steel Overall |
| Material Document And Classification: | Pwa 722,fscm 61858 Mfr Ref Single Material Response Overall |
| Surface Treatment: | Nickel Overall And Cadmium Overall |
| Thread Series Designator: | Unf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/237233> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.