

Description

Fastener Length: 1/2", Hole Diameter: 1/16", Thread: 5/16-24, Thread Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	237233
Minimum Qty (MOQ):	5 EA
NSN:	5306-00-207-7963
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N 237233 Specifications

Thread Direction:	Right-hand
Thread Length:	0.490 Inches Minimum And 0.510 Inches Maximum
Fastener Length:	0.490 Inches Minimum And 0.510 Inches Maximum
Head Style:	Double Hexagon W/hole
Head Height:	0.334 Inches Minimum And 0.354 Inches Maximum
Width Between Flats:	0.362 Inches Minimum And 0.377 Inches Maximum
Extended Washer Diameter:	0.490 Inches Minimum And 0.510 Inches Maximum
Extended Washer Thickness:	0.070 Inches Minimum And 0.090 Inches Maximum
Hole Diameter:	0.062 Inches Nominal
Nominal Thread Diameter:	0.312 Inches
Hole Quantity:	4
Hole Type:	Drilled
Features Provided:	Finished Head
Nonstandard Thread Pitch Diameter:	+0.2797/+0.2824 Inches
Nonstandard Thread Pitch Diameter:	+0.2797 To 0.2824 Inches
Thread Quantity Per Inch:	24
Hardness Rating:	30.0 Rockwell C Minimum Overall And 38.0 Rockwell C Maximum Overall
Hole Configuration Style:	Hexagon Longitudinal Hole
Material:	Steel Overall
Material Document And Classification:	Pwa 722,fscm 61858 Mfr Ref Single Material Response Overall
Surface Treatment:	Nickel Overall And Cadmium Overall
Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/237233> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.