

**Description**

length: 0.470", cadmium plated steel slotted recess

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	25012017C3C
Minimum Qty (MOQ):	10
NSN:	5325-00-281-1922
National Motor Freight:	066440, Fasteners Curtain / Snap Metal

NO IMAGE  
AVAILABLE

## P/N 2501-20-17-C3C Specifications

<b>Grip Length:</b>	0.470 Inches Nominal
<b>Diameter:</b>	0.562 Inches Nominal
<b>Turnlock Stud Shank Style:</b>	Stud Shank
<b>Turnlock Stud Head Style:</b>	Fillister
<b>Material Accommodated Thickness:</b>	0.161 Inches Minimum And 0.170 Inches Maximum
<b>Drive Type:</b>	Slotted
<b>Shank Neck Length:</b>	0.290 Inches Nominal
<b>Stud Shank Major Diameter:</b>	0.306 Inches Minimum And 0.311 Inches Maximum
<b>Material:</b>	Steel Overall
<b>Material Document And Classification:</b>	2320 Fscm 81343 Mfr Ref Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,cl 2,ty 1 Fed Spec Single Treatment Response Overall

## How to Order

Order this turnlock fastener stud from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+studs/2501-20-17-C3C> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.