

Description

length: 0.650", zinc plated steel, slotted recess, zinc trivalent clear finish, 2501-20 series stud

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	25012035Z3CT
Minimum Qty (MOQ):	10
NSN:	5325-00-763-2930
National Motor Freight:	066440, Fasteners Curtain / Snap Metal



* See page 2 for technical characteristics

P/N 2501-20-35-Z3CT Specifications

Grip Length:	0.650 Inches Nominal
Diameter:	0.557 Inches Minimum And 0.562 Inches Maximum
Securing Device Type:	Grommet
Turnlock Stud Shank Style:	Stud Shank
Turnlock Stud Head Style:	Fillister
Material Accommodated Thickness:	0.341 Inches Minimum And 0.350 Inches Maximum
Drive Type:	Slotted
Shank Neck Length:	0.490 Inches Nominal
Stud Shank Major Diameter:	0.306 Inches Minimum And 0.311 Inches Maximum
Material:	Steel Overall Or Steel Comp 8620 Overall
Material Document And Classification:	Sae 2317 Assn Std 1st Material Response Overall Or Aisi Assn Std 2nd Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 1 Cl 2 Fed Spec Single Treatment Response Overall

How to Order

Order this turnlock fastener stud from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+studs/2501-20-35-Z3CT> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.