

Description

length: 0.650", zinc plated steel, slotted recess, zinc trivalent clear finish, 2501-20 series stud

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	25012035Z3CT
Minimum Qty (MOQ):	10
NSN:	5325-00-763-2930
National Motor Freight:	066440, Fasteners Curtain / Snap Metal



\* See page 2 for technical characteristics

## P/N 2501-20-35-Z3CT Specifications

<b>Grip Length:</b>	0.650 Inches Nominal
<b>Diameter:</b>	0.557 Inches Minimum And 0.562 Inches Maximum
<b>Securing Device Type:</b>	Grommet
<b>Turnlock Stud Shank Style:</b>	Stud Shank
<b>Turnlock Stud Head Style:</b>	Fillister
<b>Material Accommodated Thickness:</b>	0.341 Inches Minimum And 0.350 Inches Maximum
<b>Drive Type:</b>	Slotted
<b>Shank Neck Length:</b>	0.490 Inches Nominal
<b>Stud Shank Major Diameter:</b>	0.306 Inches Minimum And 0.311 Inches Maximum
<b>Material:</b>	Steel Overall Or Steel Comp 8620 Overall
<b>Material Document And Classification:</b>	Sae 2317 Assn Std 1st Material Response Overall Or Aisi Assn Std 2nd Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416 Ty 1 Cl 2 Fed Spec Single Treatment Response Overall

## How to Order

Order this turnlock fastener stud from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+studs/2501-20-35-Z3CT> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.