

Description

length: 0.680", cadmium plated steel slotted recess - finish: cadmium electroplated - clear chromate

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-----------------------------|
| SKU / Model: | 25012038C3C |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5325-00-390-0775 |
| National Motor Freight: | 095190, Hardware, Noi Sub 9 |

NO IMAGE
AVAILABLE

P/N 2501-20-38-C3C Specifications

| | |
|---|---|
| Grip Length: | 0.351 Inches Minimum And 0.380 Inches Maximum |
| Diameter: | 0.557 Inches Minimum And 0.562 Inches Maximum |
| Securing Device Type: | Grommet |
| Turnlock Stud Shank Style: | Stud Shank |
| Turnlock Stud Head Style: | Flat Countersunk |
| Material Accommodated Thickness: | 0.371 Inches Minimum And 0.380 Inches Maximum |
| Drive Type: | Slotted |
| Shank Neck Length: | 0.480 Inches Minimum And 0.500 Inches Maximum |
| Stud Shank Major Diameter: | 0.306 Inches Minimum And 0.311 Inches Maximum |
| Material: | Steel Overall |
| Material Document And Classification: | Sae 2317 Assn Std Single Material Response Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 1,cl 2 Fed Spec Single Treatment Response Overall |

How to Order

Order this turnlock fastener stud from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+studs/2501-20-38-C3C> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.