

# P/N 2501-20-38-C3C

Military-Fasteners.com

#### Description

length: 0.680", cadmium plated steel slotted recess - finish: cadmium electroplated - clear chromate

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

### Order this part online

#### **Additional Information**

SKU / Model:	25012038C3C
Minimum Qty (MOQ):	10
NSN:	5325-00-390-0775
National Motor Freight:	095190, Hardware, Noi Sub 9



## P/N 2501-20-38-C3C Specifications

Grip Length:	0.351 Inches Minimum And 0.380 Inches Maximum
Diameter:	0.557 Inches Minimum And 0.562 Inches Maximum
Securing Device Type:	Grommet
Turnlock Stud Shank Style:	Stud Shank
Turnlock Stud Head Style:	Flat Countersunk
Material Accommodated Thickness:	0.371 Inches Minimum And 0.380 Inches Maximum
Drive Type:	Slotted
Shank Neck Length:	0.480 Inches Minimum And 0.500 Inches Maximum
Stud Shank Major Diameter:	0.306 Inches Minimum And 0.311 Inches Maximum
Material:	Steel Overall
Material Document And Classification:	Sae 2317 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 1,cl 2 Fed Spec Single Treatment Response Overall

### How to Order

Order this turnlock fastener stud from our inventory online by visiting <u>https://military-fasteners.com/studs/turnlock+fastener+studs/2501-20-38-C3C</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.