

**Description**

Fastener Length: 29/64", Thread: 0-80, Thread Length: 7/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	25766728
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-391-2890
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	096630, Screws Noi Brass / Bronze / Copper

NO IMAGE  
AVAILABLE

## P/N 2576672-8 Specifications

<b>Thread Class:</b>	2a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.430 Inches Minimum And 0.440 Inches Maximum
<b>Fastener Length:</b>	0.455 Inches Minimum And 0.465 Inches Maximum
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.099 Inches Minimum And 0.119 Inches Maximum
<b>Internal Drive Style:</b>	Slot
<b>Nominal Thread Diameter:</b>	0.060 Inches
<b>Thread Quantity Per Inch:</b>	80
<b>Countersink Angle:</b>	82.0 Degrees Nominal
<b>Screw Material:</b>	Copper Alloy 260 Or Copper Alloy 360
<b>Screw Material Document And Classification:</b>	Qq-b-626 Fed Spec 2nd Material Response Or Qq-b-626 Fed Spec 3rd Material Response
<b>Screw Surface Treatment:</b>	Tin
<b>Screw Surface Treatment Document And Classification:</b>	Mil-t-10727, Ty1 Mil Spec Single Treatment Response
<b>Thread Series Designator:</b>	Unf
<b>Nondefinitive Spec/std Data:</b>	1 Type And 2s Style

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/2576672-8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.