



Military-Fasteners.com

P/N 2576672-8

Description

Fastener Length: 29/64", Thread: 0-80, Thread Length: 7/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	25766728
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-391-2890
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	096630, Screws Noi Brass / Bronze / Copper



* See page 2 for technical characteristics

P/N 2576672-8 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.430 Inches Minimum And 0.440 Inches Maximum
Fastener Length:	0.455 Inches Minimum And 0.465 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.099 Inches Minimum And 0.119 Inches Maximum
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.060 Inches
Thread Quantity Per Inch:	80
Countersink Angle:	82.0 Degrees Nominal
Screw Material:	Copper Alloy 260 Or Copper Alloy 360
Screw Material Document And Classification:	Qq-b-626 Fed Spec 2nd Material Response Or Qq-b-626 Fed Spec 3rd Material Response
Screw Surface Treatment:	Tin
Screw Surface Treatment Document And Classification:	Mil-t-10727, Ty1 Mil Spec Single Treatment Response
Thread Series Designator:	Unf
Nondefinitive Spec/std Data:	1 Type And 2s Style

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/2576672-8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.