

P/N 2600-10W

Description

1/4 Turn Stud part number

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: 260010W

Minimum Qty (MOQ): 5 EA

NSN: 5325-00-641-0528

Schedule B: 7318.15.5030

ECCN: 9A991

National Motor Freight: 066440, Fasteners Curtain / Snap Metal



^{*} See page 2 for technical characteristics

P/N 2600-10W Specifications

Head Length:	0.700 Inches Minimum And 0.740 Inches Maximum
-	0.700 inches Millimani Ana 0.740 inches Maximani
Turnlock Stud Head Style:	Flat Fillister Wing
Stud Assembly Style:	Stud Assembly
Distance From Engaging Member To Largest Bearing Surface Of Head:	0.812 Inches Minimum And 0.827 Inches Maximum
Eyelet Outside Diameter:	0.244 Inches Minimum And 0.250 Inches Maximum
Eyelet Length:	0.322 Inches Nominal
Material Accommodated Thickness:	0.300 Inches Minimum And 0.329 Inches Maximum
Drive Type:	Slotted
Stud Head Height:	0.420 Inches Minimum And 0.460 Inches Maximum
Material:	Steel Comp 1009 Eyelet
Material:	Steel Comp 4037 Stud
Material:	Steel Pin
Material Document And Classification:	Astm A304 Assn Std Single Material Response Stud
Material Document And Classification:	Qq-s-698 Fed Spec Single Material Response Eyelet
Material Document And Classification:	Qq-w-470 Fed Spec Single Material Response Pin
Surface Treatment:	Cadmium Overall And Chromate Overall

How to Order

Order this 1/4 turn stud from our inventory online by visiting https://military-fasteners.com/studs/turnlock+fastener+receptacles/2600-10W and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.