

Description

1/4 Turn Stud part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	260010W
Minimum Qty (MOQ):	5 EA
NSN:	5325-00-641-0528
Schedule B:	7318.15.5030
ECCN:	9A991
National Motor Freight:	066440, Fasteners Curtain / Snap Metal



NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N 2600-10W Specifications

Head Length:	0.700 Inches Minimum And 0.740 Inches Maximum
Turnlock Stud Head Style:	Flat Fillister Wing
Stud Assembly Style:	Stud Assembly
Distance From Engaging Member To Largest Bearing Surface Of Head:	0.812 Inches Minimum And 0.827 Inches Maximum
Eyelet Outside Diameter:	0.244 Inches Minimum And 0.250 Inches Maximum
Eyelet Length:	0.322 Inches Nominal
Material Accommodated Thickness:	0.300 Inches Minimum And 0.329 Inches Maximum
Drive Type:	Slotted
Stud Head Height:	0.420 Inches Minimum And 0.460 Inches Maximum
Material:	Steel Comp 1009 Eyelet
Material:	Steel Comp 4037 Stud
Material:	Steel Pin
Material Document And Classification:	Astm A304 Assn Std Single Material Response Stud
Material Document And Classification:	Qq-s-698 Fed Spec Single Material Response Eyelet
Material Document And Classification:	Qq-w-470 Fed Spec Single Material Response Pin
Surface Treatment:	Cadmium Overall And Chromate Overall

How to Order

Order this 1/4 turn stud from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+receptacles/2600-10W> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.