

**Description**

cadmium plated steel - slotted recess, total panel thickness: 0.330"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	260011
Minimum Qty (MOQ):	5
NSN:	5325-00-641-3240

NO IMAGE  
AVAILABLE

## P/N 2600-11 Specifications

<b>Diameter:</b>	0.298 Inches Minimum And 0.308 Inches Maximum
<b>Turnlock Stud Head Style:</b>	Fillister
<b>Stud Assembly Style:</b>	Stud Assembly
<b>Distance From Engaging Member To Largest Bearing Surface Of Head:</b>	0.842 Inches Minimum And 0.857 Inches Maximum
<b>Eyelet Outside Diameter:</b>	0.244 Inches Minimum And 0.250 Inches Maximum
<b>Eyelet Length:</b>	0.322 Inches Nominal
<b>Material Accommodated Thickness:</b>	0.300 Inches Minimum And 0.359 Inches Maximum
<b>Drive Type:</b>	Slotted
<b>Material:</b>	Steel Comp 1009 Eyelet
<b>Material:</b>	Steel Comp 4037 Stud
<b>Material:</b>	Steel Pin
<b>Surface Treatment:</b>	Cadmium Overall

## How to Order

Order this camloc, 1/4 turn stud from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/2600-11> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.