

Description

cadmium plated steel - slotted recess, total panel thickness: 0.330"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | 260011 |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5325-00-641-3240 |



P/N 2600-11 Specifications

| | |
|--|---|
| Diameter: | 0.298 Inches Minimum And 0.308 Inches Maximum |
| Turnlock Stud Head Style: | Fillister |
| Stud Assembly Style: | Stud Assembly |
| Distance From Engaging Member To Largest Bearing Surface Of Head: | 0.842 Inches Minimum And 0.857 Inches Maximum |
| Eyelet Outside Diameter: | 0.244 Inches Minimum And 0.250 Inches Maximum |
| Eyelet Length: | 0.322 Inches Nominal |
| Material Accommodated Thickness: | 0.300 Inches Minimum And 0.359 Inches Maximum |
| Drive Type: | Slotted |
| Material: | Steel Comp 1009 Eyelet |
| Material: | Steel Comp 4037 Stud |
| Material: | Steel Pin |
| Surface Treatment: | Cadmium Overall |

How to Order

Order this camloc, 1/4 turn stud from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/2600-11> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.