

**Description**

Diameter: 19/64", steel overall

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	260012
Minimum Qty (MOQ):	5 EA
NSN:	5325-00-141-7951
Schedule B:	7318.15.5030
ECCN:	EAR99
National Motor Freight:	066440, Fasteners Curtain / Snap Metal

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N 2600-12 Specifications

<b>Diameter:</b>	0.298 Inches Minimum And 0.308 Inches Maximum
<b>Securing Device Type:</b>	Washer
<b>Turnlock Stud Head Style:</b>	Flat Fillister
<b>Stud Assembly Style:</b>	Stud Assembly
<b>Distance From Engaging Member To Largest Bearing Surface Of Head:</b>	0.872 Inches Minimum And 0.887 Inches Maximum
<b>Eyelet Outside Diameter:</b>	0.244 Inches Minimum And 0.250 Inches Maximum
<b>Eyelet Length:</b>	0.322 Inches Nominal
<b>Material Accommodated Thickness:</b>	0.330 Inches Minimum And 0.389 Inches Maximum
<b>Drive Type:</b>	Slotted
<b>Stud Head Height:</b>	0.093 Inches Nominal
<b>Material:</b>	Steel Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall

## How to Order

Order this 1/4 turn stud from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+receptacles/2600-12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.