

## P/N 2600-12S

### **Description**

Diameter: 19/64", steel overall

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: 260012S

Minimum Qty (MOQ): 5

NSN: 5325-00-606-8252

ECCN: EAR99

National Motor Freight: 066440, Fasteners Curtain / Snap Metal









# P/N 2600-12S Specifications

Diameter:	0.303 Inches Nominal
Securing Device Type:	Washer
Turnlock Stud Head Style:	Fillister
Stud Assembly Style:	Stud Assembly
Distance From Engaging Member To Largest Bearing Surface Of Head:	0.871 Inches Minimum And 0.887 Inches Maximum
Eyelet Outside Diameter:	0.244 Inches Minimum And 0.250 Inches Maximum
Eyelet Length:	0.322 Inches Nominal
Material Accommodated Thickness:	0.360 Inches Minimum And 0.389 Inches Maximum
Drive Type:	Slotted
Material:	Steel Overall
Surface Treatment:	Passivate Overall

## **How to Order**

Order this turnlock fastener stud assembly from our inventory online by visiting <a href="https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/2600-125">https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/2600-125</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/2600-125">https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/2600-125</a>