

Description

2600-12SW Turnlock Fastener Receptacle

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	260012SW
Minimum Qty (MOQ):	1
NSN:	5325-00-810-2971
Schedule B:	7318.15.5030
ECCN:	EAR99
National Motor Freight:	066440, Fasteners Curtain / Snap Metal

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N 2600-12SW Specifications

Head Length:	0.720 Inches Nominal
Turnlock Stud Head Style:	Fillister Wing
Stud Assembly Style:	Stud Assembly
Distance From Engaging Member To Largest Bearing Surface Of Head:	0.881 Inches Nominal
Eyelet Outside Diameter:	0.244 Inches Minimum And 0.250 Inches Maximum
Eyelet Length:	0.322 Inches Nominal
Material Accommodated Thickness:	0.330 Inches Minimum And 0.359 Inches Maximum
Stud Head Height:	0.440 Inches Nominal
Material:	Steel Comp 302 Ejector Spring
Material:	Steel Comp 302 Stud Or Steel Corrosion Resisting Stud
Material:	Steel Comp 302 Pin
Material:	Steel Comp 305 Eyelet
Material Document And Classification:	Qq-s-763 Fed Spec 1st Material Response Stud Or Carpenter No. 10 Cagc 71321 Mfr Ref 2nd Material Response Stud
Material Document And Classification:	Qq-s-763 Fed Spec Single Material Response Ejector Spring
Material Document And Classification:	Qq-s-763 Fed Spec Single Material Response Pin
Material Document And Classification:	Qq-s-766 Fed Spec Single Material Response Eyelet
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall

How to Order

Order this turnlock fastener receptacle from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+receptacles/2600-12SW> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.