

Description

corrosion resistant steel - winged - total panel thickness 0.360" - 0.389"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	260012W
Minimum Qty (MOQ):	1
NSN:	5325-00-638-9069
National Motor Freight:	066440, Fasteners Curtain / Snap Metal

NO IMAGE
AVAILABLE

P/N 2600-12W Specifications

Head Length:	0.700 Inches Minimum And 0.740 Inches Maximum
Turnlock Stud Head Style:	Fillister Wing
Stud Assembly Style:	Stud Assembly
Distance From Engaging Member To Largest Bearing Surface Of Head:	0.872 Inches Minimum And 0.887 Inches Maximum
Eyelet Outside Diameter:	0.244 Inches Minimum And 0.250 Inches Maximum
Eyelet Length:	0.322 Inches Nominal
Material Accommodated Thickness:	0.361 Inches Minimum And 0.390 Inches Maximum
Stud Head Height:	0.420 Inches Minimum And 0.460 Inches Maximum
Material:	Steel Comp 1009 Eyelet
Material:	Steel Comp 4037 Stud
Material:	Steel Ejector Spring
Material:	Steel Pin
Material Document And Classification:	Astm A109 Assn Std Single Material Response Eyelet
Material Document And Classification:	Astm A547 Assn Std Single Material Response Stud
Material Document And Classification:	Qq-w-470 Fed Spec Single Material Response Ejector Spring
Material Document And Classification:	Qq-w-470 Fed Spec Single Material Response Pin
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall

How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/2600-12W> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.