

Description

Diameter: 19/64", steel overall

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	260014S
Minimum Qty (MOQ):	5 EA
NSN:	5325-00-682-1672
Schedule B:	7318.15.5030
ECCN:	EAR99
National Motor Freight:	066440, Fasteners Curtain / Snap Metal

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N 2600-14S Specifications

Diameter:	0.298 Inches Minimum And 0.308 Inches Maximum
Securing Device Type:	Spring
Turnlock Stud Head Style:	Fillister Countersunk
Stud Assembly Style:	Stud Assembly
Distance From Engaging Member To Largest Bearing Surface Of Head:	0.938 Inches Nominal
Eyelet Outside Diameter:	0.305 Inches Minimum And 0.315 Inches Maximum
Eyelet Length:	0.322 Inches Nominal
Material Accommodated Thickness:	0.420 Inches Minimum And 0.449 Inches Maximum
Drive Type:	Slotted
Stud Head Height:	0.078 Inches Minimum And 0.093 Inches Maximum
Material:	Steel Overall

How to Order

Order this 1/4 turn stud from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+receptacles/2600-14S> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.