

Description

Diameter: 19/64", steel overall

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	260015
Minimum Qty (MOQ):	10 EA
NSN:	5325-00-298-6999
Schedule B:	7318.16.0030
ECCN:	EAR99

NO IMAGE
AVAILABLE

P/N 2600-15 Specifications

Diameter:	0.302 Inches Nominal
Securing Device Type:	Washer
Turnlock Stud Head Style:	Flat Fillister
Stud Assembly Style:	Stud Assembly
Distance From Engaging Member To Largest Bearing Surface Of Head:	0.962 Inches Minimum And 0.977 Inches Maximum
Eyelet Outside Diameter:	0.244 Inches Minimum And 0.250 Inches Maximum
Eyelet Length:	0.322 Inches Nominal
Material Accommodated Thickness:	0.420 Inches Minimum And 0.479 Inches Maximum
Drive Type:	Slotted
Stud Head Height:	0.930 Inches Nominal
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall

How to Order

Order this 1/4 turn stud from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+receptacles/2600-15> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.