

Description

corrosion resistant steel - slotted recess - total panel thickness 0.510" - 0.539"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | 260017S |
| Minimum Qty (MOQ): | 2 |
| NSN: | 5325-00-778-7724 |



* See page 2 for technical characteristics

P/N 2600-17S Specifications

| | |
|---|---|
| Diameter: | 0.250 Inches Nominal |
| Securing Device Type: | Washer |
| Turnlock Stud Head Style: | Err-090 |
| Stud Assembly Style: | Stud Assembly |
| Distance From Engaging Member To Largest Bearing Surface Of Head: | 0.915 Inches Nominal |
| Eyelet Outside Diameter: | 0.247 Inches Nominal |
| Eyelet Length: | 0.328 Inches Nominal |
| Material Accommodated Thickness: | 0.531 Inches Minimum And 0.560 Inches Maximum |
| Drive Type: | Slotted |
| Stud Head Height: | 0.073 Inches Nominal |
| Material: | Steel Overall |
| Surface Treatment: | Passivate Overall |

How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/2600-17S> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.