

Description

corrosion resistant steel - slotted recess - total panel thickness 0.510" - 0.539"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	260017S
Minimum Qty (MOQ):	2
NSN:	5325-00-778-7724

NO IMAGE
AVAILABLE

P/N 2600-17S Specifications

Diameter:	0.250 Inches Nominal
Securing Device Type:	Washer
Turnlock Stud Head Style:	Err-090
Stud Assembly Style:	Stud Assembly
Distance From Engaging Member To Largest Bearing Surface Of Head:	0.915 Inches Nominal
Eyelet Outside Diameter:	0.247 Inches Nominal
Eyelet Length:	0.328 Inches Nominal
Material Accommodated Thickness:	0.531 Inches Minimum And 0.560 Inches Maximum
Drive Type:	Slotted
Stud Head Height:	0.073 Inches Nominal
Material:	Steel Overall
Surface Treatment:	Passivate Overall

How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/2600-17S> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.