

P/N 2600-18

Description

Diameter: 19/64", steel comp 4037 stud

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	260018
Minimum Qty (MOQ):	5 EA
NSN:	5325-01-521-5476
Schedule B:	7318.15.5030
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi



^{*} See page 2 for technical characteristics

P/N 2600-18 Specifications

Diameter:	0.298 Inches Minimum And 0.308 Inches Maximum
Securing Device Type:	Spring
End Item Identification:	Na-kit
Turnlock Stud Head Style:	Flat Fillister
Stud Assembly Style:	Stud Assembly
Distance From Engaging Member To Largest Bearing Surface Of Head:	1.021 Inches Minimum And 1.036 Inches Maximum
Eyelet Outside Diameter:	0.305 Inches Minimum And 0.315 Inches Maximum
Eyelet Length:	0.322 Inches Nominal
Drive Type:	Slotted
Stud Head Height:	0.088 Inches Minimum And 0.098 Inches Maximum
Material:	Steel Comp 4037 Stud
Material Document And Classification:	Qq-s-624, 4037 Fed Spec Single Material Response Stud
Surface Treatment:	Cadmium Stud
Surface Treatment Document And Classification:	Qq-p-416, Cl2 Type li Fed Spec Single Treatment Response Stud

How to Order

Order this 1/4 turn stud from our inventory online by visiting https://military-fasteners.com/studs/turnlock+fastener+receptacles/2600-18 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/studs/turnlock+fastener+receptacles/2600-18 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/studs/turnlock+fastener+receptacles/2600-18 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/studs/turnlock+fastener-track-to-tale-t