

**Description**

Diameter: 19/64", steel comp 4037 stud

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	260018
Minimum Qty (MOQ):	5 EA
NSN:	5325-01-521-5476
Schedule B:	7318.15.5030
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi



\* See page 2 for technical characteristics

## P/N 2600-18 Specifications

<b>Diameter:</b>	0.298 Inches Minimum And 0.308 Inches Maximum
<b>Securing Device Type:</b>	Spring
<b>End Item Identification:</b>	Na-kit
<b>Turnlock Stud Head Style:</b>	Flat Fillister
<b>Stud Assembly Style:</b>	Stud Assembly
<b>Distance From Engaging Member To Largest Bearing Surface Of Head:</b>	1.021 Inches Minimum And 1.036 Inches Maximum
<b>Eyelet Outside Diameter:</b>	0.305 Inches Minimum And 0.315 Inches Maximum
<b>Eyelet Length:</b>	0.322 Inches Nominal
<b>Drive Type:</b>	Slotted
<b>Stud Head Height:</b>	0.088 Inches Minimum And 0.098 Inches Maximum
<b>Material:</b>	Steel Comp 4037 Stud
<b>Material Document And Classification:</b>	Qq-s-624, 4037 Fed Spec Single Material Response Stud
<b>Surface Treatment:</b>	Cadmium Stud
<b>Surface Treatment Document And Classification:</b>	Qq-p-416, Cl2 Type Ii Fed Spec Single Treatment Response Stud

## How to Order

Order this 1/4 turn stud from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+receptacles/2600-18> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.