

P/N 2600-18S

Description

Diameter: 19/64", steel corrosion resisting overall

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	2600185
Minimum Qty (MOQ):	5 EA
NSN:	5325-01-587-2608
Schedule B:	7318.15.2091
ECCN:	EAR99



^{*} See page 2 for technical characteristics

P/N 2600-18S Specifications

Diameter:	0.303 Inches Nominal
Turnlock Stud Head Style:	Flat Fillister
Stud Assembly Style:	Stud Assembly
Distance From Engaging Member To Largest Bearing Surface Of Head:	1.270 Inches Nominal
Material Accommodated Thickness:	0.540 Inches Minimum And 0.569 Inches Maximum
Drive Type:	Slotted
Material:	Steel Corrosion Resisting Overall

How to Order

Order this 1/4 turn stud from our inventory online by visiting https://military-fasteners.com/studs/turnlock+fastener+receptacles/2600-185 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/studs/turnlock+fastener+receptacles/2600-185 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/studs/turnlock+fastener+receptacles/2600-185 and selecting the