

Description

Diameter: 19/64", steel ejector spring

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	260021
Minimum Qty (MOQ):	5 EA
NSN:	5325-00-619-7051
Schedule B:	7318.15.5030
ECCN:	EAR99
National Motor Freight:	066440, Fasteners Curtain / Snap Metal



* See page 2 for technical characteristics

P/N 2600-21 Specifications

Diameter:	0.298 Inches Minimum And 0.308 Inches Maximum
Turnlock Stud Head Style:	Flat Fillister
Stud Assembly Style:	Stud Assembly
Distance From Engaging Member To Largest Bearing Surface Of Head:	1.142 Inches Minimum And 1.157 Inches Maximum
Eyelet Outside Diameter:	0.244 Inches Minimum And 0.250 Inches Maximum
Eyelet Length:	0.322 Inches Nominal
Material Accommodated Thickness:	0.570 Inches Minimum And 0.659 Inches Maximum
Drive Type:	Slotted
Stud Head Height:	0.088 Inches Minimum And 0.098 Inches Maximum
Material:	Steel Comp 1008 Eyelet Or Steel Comp 1009 Eyelet Or Steel Comp 1015 Eyelet Or Steel Comp 1018 Eyelet Or Steel Comp 1018 Eyelet Or Steel Comp 1020 Eyelet
Material:	Steel Comp 4037 Stud
Material:	Steel Ejector Spring
Material:	Steel Pin
Material Document And Classification:	Astm A322 Assn Std 1st Material Response Stud Or Astm A331 Assn Std 2nd Material Response Stud
Material Document And Classification:	Qq-s-698 Fed Spec Single Material Response Eyelet
Material Document And Classification:	Qq-w-470 Fed Spec Single Material Response Ejector Spring
Material Document And Classification:	Qq-w-470 Fed Spec Single Material Response Pin
Surface Treatment:	Cadmium Overall

How to Order

Order this 1/4 turn stud from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+receptacles/2600-21> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.