

Description

Diameter: 19/64", steel overall

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|--|
| SKU / Model: | 260023 |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5325-00-067-3517 |
| Schedule B: | 7318.15.5030 |
| ECCN: | EAR99 |
| National Motor Freight: | 066440, Fasteners Curtain / Snap Metal |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N 2600-23 Specifications

| | |
|--|---|
| Diameter: | 0.298 Inches Minimum And 0.308 Inches Maximum |
| Securing Device Type: | Washer |
| Turnlock Stud Head Style: | Flat Fillister |
| Stud Assembly Style: | Stud Assembly |
| Distance From Engaging Member To Largest Bearing Surface Of Head: | 1.211 Inches Nominal |
| Eyelet Outside Diameter: | 0.247 Inches Nominal |
| Eyelet Length: | 0.322 Inches Nominal |
| Material Accommodated Thickness: | 0.690 Inches Minimum And 0.719 Inches Maximum |
| Drive Type: | Slotted |
| Stud Head Height: | 0.088 Inches Minimum And 0.098 Inches Maximum |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |

How to Order

Order this turnlock fastener receptacle from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+receptacles/2600-23> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.