

P/N 2600-24

Description

Diameter: 19/64", steel stud

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: 260024

Minimum Qty (MOQ): 5 EA

NSN: 5325-00-965-8449

Schedule B: 7318.15.5030

ECCN: EAR99

National Motor Freight: 066440, Fasteners Curtain / Snap Metal



^{*} See page 2 for technical characteristics

P/N 2600-24 Specifications

Diameter:	0.298 Inches Minimum And 0.308 Inches Maximum
Turnlock Stud Head Style:	Fillister
Stud Assembly Style:	Stud Assembly
Distance From Engaging Member To Largest Bearing Surface Of Head:	1.233 Inches Minimum And 1.248 Inches Maximum
Eyelet Outside Diameter:	0.244 Inches Minimum And 0.250 Inches Maximum
Eyelet Length:	0.322 Inches Nominal
Material Accommodated Thickness:	0.720 Inches Minimum And 0.749 Inches Maximum
Drive Type:	Slotted
Material:	Steel Comp 1009 Eyelet
Material:	Steel Pin
Material:	Steel Stud
Material Document And Classification:	Astm A304 Assn Std Single Material Response Stud
Material Document And Classification:	Qq-s-698 Fed Spec Single Material Response Eyelet
Material Document And Classification:	Qq-w-470 Fed Spec Single Material Response Pin
Surface Treatment:	Cadmium Overall And Chromate Overall

How to Order

Order this 1/4 turn stud from our inventory online by visiting https://military-fasteners.com/studs/turnlock+fastener+receptacles/2600-24 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.